



Motion® CL900 SlateMate™

With Magnetic Stripe Reader and Barcode Scanner

Check inventory, process payments and capture data anywhere on the sales floor with the Motion® CL900 SlateMate™, an industry-first integrated expansion solution that transforms the CL900 Tablet PC into a mobile-point-of-sale (MPOS) and data acquisition tool. The CL900 SlateMate with Magnetic Stripe Reader (MSR) and Barcode Scanner (BCS) is securely integrated into the internal frame of the CL900, serving as a streamlined productivity solution that doesn't require connections to third party devices.

SlateMate for Retail

The CL900 with SlateMate is the ideal solution for retailers to improve customer satisfaction, increase workforce productivity and enhance data integrity. Serving as a MPOS terminal, the CL900 with MSR and BCS combines the ability to process payments, manage inventory status, or gain insight into customer details directly at the point of service.



The CL900 SlateMate with MSR and BCS enables:

- Improved customer satisfaction and loyalty
- Enhanced store experience
- Empowered store associates and knowledgeable advisors
- Improved transaction times
- Reduced customer abandon rates
- Expanded transaction capabilities during peak periods
- Increased revenue per transaction

With the ability to read virtually all barcodes used by retailers, the CL900 SlateMate offers seamless, reliable, fast and managed scanning. Additionally, because it uses MagTek® MSR technology, certified with most payment processors, the vast majority of retailers will be able to easily deploy the MSR in their environments. The CL900 SlateMate with MSR and BCS provides the battery life, connectivity and PCI requirements retailers need to thrive in today's challenging business environments.



Motion® CL900 SlateMate™

With Magnetic Stripe Reader and Barcode Scanner

PRODUCT SPECIFICATIONS

Barcode Scanner 1D/2D Barcode Scanner
Enabled Barcode Symbolologies:
Code 39, Code 128, UPC-A, UPC-E, Interleaved 2 of 5
MicroPDF417, PDF417, QR Code
Additional symbolologies can be configured.
Contact Motion for more information.

Mag Stripe Reader • Reads 1, 2 & 3 Track Cards per ISO 7810 & 7811
and AAMVA

**Mag Stripe Data
Encryption Standards** • TDES

**Key Management
Standards** • DUKPT

**Expansion &
Docking Compatibility** • Compatible with CL900 Docking Station

Buttons & Indicators • Barcode Scan button
• Integrated beeper
- Barcode Scan confirmation
• MSR LED

Dimensions • L (332mm) H (180mm) W (15.4mm)

Weight • Weight = 135 g (.3 lb)

Durability • MIL-STD-810G, Method 516.6, Procedure IV (Transit Drop)
• IP52

OS support • Genuine Windows® 7 Professional (32-bit)
• Genuine Windows® 7 Home Premium (32-bit)

**EMI, Safety, &
Environmental
Regulations** • ANSI C63.4
• FCC Part 15B
• ICES-003 Class B
• CENELEC EN55022 Class B (CISPR 22)
• CENELEC EN 55024 (CISPR 24)
• AS/NZS 3548 Class B
• 2002/95/EC (ROHS)
• 2002/96/EC (WEEE)
• Art. 59.1 of Regulation 1907/2006 {SVHC} (REACH)
• Proposition 65
• IEC 60950-1 2nd Edition (UL, CUL)
• EN 60950-1 2nd Edition (CE, Nemko, TUV)

Specifications • Operation Temperature: 0 ~ +43C
• Storage Temperature: -10 ~ +60C
• Humidity: 5% to 95% (Non Condensing)
• Mag Head operating life: 500K cycles Min.
• Card operating speed: 4 IPS ~ 40 IPS.

